

10th ed 1 G

10 JUL 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 July 2004 (29.07.2004)

PCT

(10) International Publication Number
WO 2004/063602 A1

(51) International Patent Classification⁷: **F16H 61/00,**
37/08

William, Edward [GB/GB]; 25 Broadgate, Preston PR1
8DX (GB).

(21) International Application Number:
PCT/GB2004/000042

(74) Agent: **W.P. THOMPSON & CO**; Coopers Building,
Church Street, Liverpool L1 3AB (GB).

(22) International Filing Date: 8 January 2004 (08.01.2004)

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0300419.9 9 January 2003 (09.01.2003) GB

(71) Applicant (*for all designated States except US*): **TORO-TRAK (DEVELOPMENT) LTD** [GB/GB]; 1 Aston Way, Leyland, Lancashire PR5 3UX (GB).


(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **FULLER, John,**

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: CONTINUOUSLY VARIABLE TRANSMISSION



(57) Abstract: A continuously variable transmission is disclosed comprising a transmission input and output between which a variator (V) can be coupled, in either a low regime or a high regime, by gearing (R1, R2, R3, M). The relationship between variator ratio and overall transmission ratio is different in the two regimes. Incorporated in the gearing are first and second clutch means (L, H) both hydraulically actuated, for engaging and disengaging low and high regimes respectively. The gearing provides a synchronous ratio at which a change between low and high regimes, at constant variator ratio, provides no change in the overall transmission ratio. The transmission is provided with hydraulics which incorporate a shift valve (110) which controls application of hydraulic pressures to the first and second clutch means. A change in state of the shift valve (110) causes one clutch means to change from engaged to disengaged and the other to make the opposite transition. In this way changes of transmission regime are hydraulically controlled.

WO 2004/063602 A1